



D-2 Emulsion
 Material Safety Data Sheet
 Issued: 4/28/06
 Supercedes: 2/20/04

Section I - Chemical Product and Company Identification

Manufacturers name IKONICS Corporation
 Address 4832 Grand Avenue, Duluth, MN 55807
 Telephone number 218 628-2217 Customer Service
 Emergency phone number 800 424-9300 Chemtrec USA / 703/527-3887 International (collect)
 Product name D-2 Emulsion
 Use Transfer emulsion

Section II – Hazardous Ingredients

<u>Ingredients</u>	<u>Percent</u>	<u>CAS#</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>VAPOR PSI</u>
Isopropanol	≤ 8.5%	67-63-0	400 ppm	980 mg/M ³	30.9 mm/Hg. 20°C

Section III – Physical Data

Appearance White colored liquid emulsion.
 Boiling point 200° F- 215° F
 Weight (per gallon) 8.70 lb/gal.
 Percent volatile (by wt) .75%
 Solubility in water 100% dispersible
 Evaporation rate Not Established
 Vapor density Not Established
 VOC 88.72 g/l

Section IV – Fire and Explosion Data

Flash point 100°F
 Extinguishing media Foam, CO₂, dry chemical, or water spray.
 Unusual fire & explosion hazards None
 Special fire fighting procedures None

Section V – Health Hazard Data

HMIS Codes 1-0-0-B Minimal=0, Slight=1, Moderate=2, Serious=3, Severe=4

Effects of overexposure

Eye contact No specific information available. Eye contact will cause irritation.
 Skin contact No specific information available. May cause irritation.
 Inhalation No specific information available.
 Ingestion No specific information available.

First aid emergency procedures

Eye Flush with plenty of water for at least 15 minutes and seek medical attention.
 Skin Wash with soap and water, should irritation occur, seek medical attention.
 Inhalation Remove to fresh air.
 Ingestion If appreciable quantities are swallowed, seek medical attention

Section VI – Reactivity Data

Stability	Unstable ___ Stable <u>X</u>
Conditions to avoid	None
Incompatibility (materials to avoid)	None
Hazardous decomposition products	Prolonged exposure to heat may yield aldehydes, acetic acid and oxides of carbon.
Hazardous polymerization	May occur ___ Will not occur <u>X</u>

Section VII – Spill or Leak Procedures

Spill cleanup instructions	Contain and remove with inert absorbent material. Caution: Liquid emulsion and diluted emulsion can pose a potential slippage problem in walkways. Use proper PPE when cleaning up a spill.
Waste disposal method	Dispose of in accordance with federal, state, and local laws.

We make no guarantee or warranty of any kind that the use or disposal of this product is in compliance with all federal, state, or local laws. It is the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

Section VIII – Control Measures / Personal Protection

Engineering controls	Ventilation – Local exhaust recommended but not required. Provide adequate ventilation as necessary.
<i>Personal Protection Equipment (PPE)</i>	
Gloves	Rubber or neoprene gloves are recommended.
Eye	Personal eye protection is recommended.
Respiratory	Not required.
Where contact may occur	Use proper PPE.
Safety shower and eyewash	Should be available.

Section IX – Handling and Storage

Handling and storage information	Store between 50°F- 80°F for maximum storage life.
Other precautions	Industrial use only. Keep out of reach of children. Do not take internally. Avoid splashing in eyes.

Section X – Regulation Information

DOT classification	Not a DOT controlled material (United States). Does not sustain combustion according to ASTM 4206 or Appendix H procedures in 49 CFR 173.120 (a) (3).
TSCA	All ingredients are listed chemicals in the TSCA registry.
California (Prop 65)	This product contains chemical(s) known to the State of California to cause cancer (c) or reproductive (r) damage. <0.00095% Acetaldehyde (c) 75-07-0 Listed April 1, 1988 <0.0006% Ethylene oxide (c) 75-21-8 Listed July 1, 1987 <0.0006% Hydrazine (c) 302-01-2 Listed January 1, 1988 <0.0001% Methyl Iodine (c) 74-88-4 Listed April 1, 1988 <0.00055% Toluene (r) 108-88-3 Listed January 1, 1991

Approved by: VP Technology, Toshi Komatsu 218 628-2217 ext.142

Notice to reader

(Approved by U.S. Department of Labor “Essentially Similar” to form OSHA-20)

The information contained herein is based on data available to us and is believed to be correct. Since this information may have been obtained in part from independent laboratories or other sources not under direct supervision, no representation is made that the information is accurate, reliable, complete, or representative and Buyer may rely thereon only at the Buyer’s risk. We make no guarantee that the health and safety precautions we have suggested will be adequate for all individuals and / or situations involving its handling and uses. No warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Vendor assumes no responsibility for injury to vendee or third person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet.