



SBX Liquid Emulsion
 Material Safety Data Sheet
 Issued: 3/31/04
 Supercedes: 7/17/01

Section I - Chemical Product and Company Identification

Manufacturers name IKONICS Corporation
 Address 4832 Grand Avenue, Duluth, MN 55807
 Telephone number 218 628-2217 Customer Service
 Emergency phone number 800 424-9300 Chemtrec USA / 703/527-3887 International (collect)
 Product name SBX Liquid Emulsion
 Use Sandblast Emulsion

Section II – Hazardous Ingredients

<u>Ingredients</u>	<u>Percent</u>	<u>CAS#</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>VAPOR PSI</u>
There are no hazardous ingredients by reference to the O.S.H.A. Hazardous Communications Standard (29 CFR 1910.1200)	Not Applicable	-----	-----	-----	-----

Section III – Physical Data

Appearance White or violet emulsion
 Boiling point 94°C-102°C (200° F -215° F)
 Weight (per gallon) 8.70 lb/gal.
 Percent volatile (by wt) 75%
 Solubility in water 100% dispersible
 Evaporation rate Not Established
 Vapor density Not Established
 VOC Not Applicable

Section IV – Fire and Explosion Data

Flash point Not Applicable
 Extinguishing media Non-flammable in liquid state. When dry, use CO₂ dry chemical, or water.
 Unusual fire & explosion hazards None
 Special fire fighting procedures None

Section V – Health Hazard Data

HMIS Codes 0-1-0-B Minimal=0, Slight=1, Moderate=2, Serious=3, Severe=4

Effects of overexposure

Eye contact No specific information available.
 Skin contact No specific information available. May cause skin injury.
 Inhalation No specific information available.
 Ingestion No specific information available.

First aid emergency procedures

Eye Flush with plenty of water for at least 15 minutes and seek medical attention.
 Skin Wash with soap and water, should irritation occur, seek medical attention.
 Inhalation Remove to fresh air.
 Ingestion If appreciable quantities are swallowed, seek medical attention.

Section VI – Reactivity Data

Stability	Unstable ___ Stable <u>X</u>
Conditions to avoid	None known.
Incompatibility (materials to avoid)	None known.
Hazardous decomposition products	Prolonged exposure to heat may yield aldehydes, acetic acid, and oxides of carbon.
Hazardous polymerization	May occur ___ Will not occur <u>X</u>

Section VII – Spill or Leak Procedures

Spill cleanup instructions	Contain spills with absorbent material and dispose of saturated material.
Waste disposal method	Place leaking container in a well ventilated area. Dilute the spill with water and absorb the spill with inert material and dispose in accordance with federal, state, and local laws. Use proper PPE when cleaning up a spill. Liquid emulsion can pose a potential slippage problem.

We make no guarantee or warranty of any kind that the use or disposal of this product is in compliance with all federal, state, or local laws. It is the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

Section VIII – Control Measures / Personal Protection

Engineering controls	Ventilation – Local exhaust recommended but not required.
<i>Personal Protection Equipment (PPE)</i>	
Gloves	Recommended.
Eye	Recommended.
Respiratory	Not required.
Where contact may occur	Use the proper PPE.
Safety shower and eyewash	Should be available.

Section IX – Handling and Storage

Handling and storage information	None.
Other precautions	Industrial use only. Keep out of reach of children. Do not take internally. Avoid splashing in eyes.

Section X – Regulation Information

DOT classification	Not a DOT controlled material (United States).
TSCA	All ingredients are listed chemicals in the TSCA registry.
California (Prop 65)	This product contains chemical(s) known to the State of California to cause cancer (c) or reproductive (r) damage. <0.0003% Acetaldehyde (c) 75-07-0 Listed April 1, 1988 <0.0002% Ethylene oxide (c) 75-21-8 Listed July 1, 1987 <0.0002% Hydrazine (c) 302-01-2 Listed January 1, 1988 <0.0001% Toluene (r) 108-88-3 Listed January 1, 1991 <0.0004% 1,4 Dioxane (c) 123-91-1 Listed January 1, 1988

Approved by: VP Technology, Toshi Komatsu 218 628-2217 ext.142

Notice to reader

(Approved by U.S. Department of Labor “Essentially Similar” to form OSHA-20)

The information contained herein is based on data available to us and is believed to be correct. Since this information may have been obtained in part from independent laboratories or other sources not under direct supervision, no representation is made that the information is accurate, reliable, complete, or representative and Buyer may rely thereon only at the Buyer’s risk. We make no guarantee that the health and safety precautions we have suggested will be adequate for all individuals and / or situations involving its handling and uses. No warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Vendor assumes no responsibility for injury to vendee or third person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet.