

CHROMA/LAST™

Chromaline Hardener EH-A & EH-B

CHROMA/LAST

- Two parts emulsion hardener.
- Ideal for making many types of emulsions permanent.
- Non-Flammable.



STANDARD SIZES

Gallon

SPECIFICATIONS

Appearance: Clear
Consistency: Liquid

SAFETY AND HANDLING

For industrial use only. Keep out of the reach of children. Refer to MSDS.

Irritation may result upon contact with skin and eyes. Use of rubber gloves and eye/face protection are required. Use with adequate ventilation. Keep container closed when not in use.

FIRST AID

EYES: Flush eyes with plenty of water. If irritation persists, consult a physician.
SKIN: Wash exposed area well with water.
INGESTION: Get medical attention.
INHALATION: Remove to fresh air.

DIRECTIONS

1. Mix EH-A and EH-B together in equal parts (1:1). Once mixed the shelf of the mixture is approximately 18-24 hours.
2. Brush or wipe the solution onto a dry imaged screen. Let dry at least 15 minutes (depending on conditions) at room temp to allow the solution to penetrate into the stencil.
3. Let the treated stencil dry overnight at room temperature to fully harden the stencil. The hardener will evaporate out of the open image areas. To accelerate the activation time: dry at least 1 hour at 100°F (40°C).
4. Once cured, the stencil is permanent and cannot be reclaimed.



Chromaline Screen Print Products

4832 Grand Ave. • Duluth, Minnesota 55807 • Tel: 218-628-2217 • Fax: 218.628.3245
Web Site: www.chromaline.com • E-mail: sales@chromaline.com