

HEALTH & SAFETY: Before using, refer to the appropriate [Safety Data Sheets](#).

STORAGE: When sealed in the original container and stored in cool conditions, Chromaline's integrated Screen Chemistry will maintain their original properties for two years from the date of production.

Chroma/Wet™ iSC

DEGREASER / ADHESION PROMOTER

- Powerful detergent and degreaser to restore mesh after reclaiming
- Blue color ensures complete rinse from mesh
- Eliminates fisheyes and streaks in coatings
- Promotes adhesion for both emulsion and capillary film stencils
- Optimizes resolution, definition and stencil life

Available formats: quart, gallon

Degreaser LF iSC

LOW FOAMING CONCENTRATE

- 10 to 1 concentrated liquid wetting agent and degreaser
- Light brown color ensures complete rinse from mesh
- 100% Biodegradable
- Low foaming; ideal for use in automatic machines
- Eliminates fisheyes and streaks in coatings
- Promotes adhesion for both emulsion and capillary film stencils
- Optimizes resolution, definition and stencil life

Available formats: quart, gallon, 5 gallon

Degreaser 260 iSC

DEGREASER / INK DEGRADER / DEHAZER

DEGREASER:

- Super concentrated with surfactants and citrus solvents
- Removes residual hand oils and printing inks

INK DEGRADER:

- Emulsifies plastisol, UV, solvent-based and water-based inks for easy water removal before reclaiming
- Safe, water-based formula / non-flammable
- Pleasant fragrance
- Cleans squeegees, flood bars, frames, etc.

DEHAZER:

- Reduces ink haze
- Remove old images from polyester
- Non-caustic formula does not degrade mesh
- Does not deteriorate mesh like caustic products

Available formats: quart, gallon, 5 gallon

DIRECTIONS FOR USE

For new stainless-steel mesh or for previously abraded synthetic monofilament mesh, apply **Chroma/Wet™ iSC** liberally to both sides of wet or dry screen with a brush or sponge. Rinse the screen with a strong water spray to remove all traces of **Chroma/Wet™ iSC**. Dry the clean freshly prepared screens and use immediately or store in a dust-free environment.

DIRECTIONS FOR USE

Mix one-part **Degreaser LF iSC** with 10 parts water. For new multifilament synthetic or stainless-steel mesh or for previously abraded synthetic monofilament mesh, apply **Degreaser LF iSC** liberally to both sides of wet or dry screen with a brush or sponge. Rinse the screen with a strong water spray to remove all traces of **Degreaser LF iSC**. Dry the clean freshly prepared screens and use immediately or store in a dust-free environment.

DIRECTIONS FOR USE

DEGREASING: After removing stencil with image mate Reclaimer 660, apply **Degreaser 260 iSC** to wet screen. **Degreaser 260 iSC** will cling to the screen. Using a clean nylon scrub pad or brush, spread **Degreaser 260 iSC** with light agitation in a circular motion. Work up lather on both sides of the screen. **Degreaser 260 iSC** may be left on screen to dwell while wet. Rinse with a garden hose.

INK DEGRADING: Remove excess ink from screen. Apply an amount of **Degreaser 260 iSC** to cover residual ink. Using dedicated nylon scrub pad or brush, agitate in a circular motion on both sides of the screen. Ink will immediately emulsify. Rinse with water.

DEHAZING: Apply **Degreaser 260 iSC** to open image areas. Scrub with dedicated nylon scrub pad or brush. If area has been stained for an extended time, allow **Degreaser 260 iSC** to penetrate for 2 to 5 minutes. Follow up with scrubbing: rinse with water. Pressure wash if necessary.

***Caution: Irritant.** Avoid eye or skin contact, keep out of reach of children. Refer to container label or SDS for additional information



PRINT WITH CONFIDENCE



integrated Screen Chemistry

help@chromaline.com | www.chromaline.com

(800) 328-4261 | International: +1-218-628-2217

ISC DEGREASERS

ISC BLOCKOUTS

ISC PRESS WASHES

ISC SCREEN WASHES

ISC STENCIL REMOVERS

ISC HAZE REMOVER

HEALTH & SAFETY: Before using, refer to the appropriate [Safety Data Sheets](#).

STORAGE: When sealed in the original container and stored in cool conditions, Chromaline's integrated Screen Chemistry will maintain their original properties for two years from the date of production.

Chroma/Fill™ Red *ISC*

SCREEN BLOCKOUT

Applications

Screen filler / block-out for touching up stencil pinholes and perimeter open areas.

Characteristics

- For use with solvent-based, UV and plastisol inks
- Coats smoothly, dries fast with optimal transparency
- Does not contain solvents and can be simply removed with water

Available formats: quart, gallon

Features/Benefits

- Fully solvent resistant and offers increased durability
- Spreads uniformly and evenly for optimal drying and filling
- Does not contain solvents and can be simply removed with water

DIRECTIONS FOR USE

On the substrate side of the screen, spread **Chroma/Fill™ Red *ISC*** evenly over desired area of mesh and stencil with a straight edge. A card or a plastic spreader is typically used. Filler may be thinned with water for retouching pinholes with a brush. To reclaim, remove with water.

Chroma/Fill™ Blue *ISC*

HIGH VISCOSITY BLOCKOUT

Applications

Screen filler / block-out for touching up stencil pinholes and perimeter open areas.

Characteristics

- For use with solvent-based, UV and plastisol inks
- Coats smoothly, dries fast with optimal transparency
- Does not contain solvents and can be simply removed with water

Available formats: quart, gallon

Features/Benefits

- High solids content for reduced shrinkage on drying and increased filling power
- Fully solvent resistant and offers increased durability
- Optimized for use on low & medium mesh counts

DIRECTIONS FOR USE

On the substrate side of the screen, spread **Chroma/Fill™ Blue *ISC*** evenly over desired area of mesh and stencil with a straight edge. A card or a plastic spreader is typically used. Filler may be thinned with water for retouching pinholes with a brush. To reclaim, remove with water.

ISC DEGREASERS

ISC BLOCKOUTS

ISC PRESS WASHES

ISC SCREEN WASHES

ISC STENCIL REMOVERS

ISC HAZE REMOVER



help@chromaline.com | www.chromaline.com

(800) 328-4261 | International: +1-218-628-2217

HEALTH & SAFETY: Before using, refer to the appropriate [Safety Data Sheets](#).

STORAGE: When sealed in the original container and stored in cool conditions, Chromaline's integrated Screen Chemistry will maintain their original properties for two years from the date of production.

Textile Press Wash *ISC*

FOR TEXTILE INKS

Applications

Removes ink from the screen for quick color changes or clearing ink from stencil openings while on press.

Characteristics

- Recommended for use with Plastisol and UV inks
- Flash point 49°C/120°F Features/Benefits
- Medium drying speed

Available formats: quart, gallon, 5 gallon, 55 gallon

DIRECTIONS FOR USE

Apply press wash directly to the screen with a low pressure sprayer, or a saturated wiping cloth. Wipe in a circular motion until ink has cleared. Allow to evaporate and continue printing.

Graphics Press Wash *ISC*

FOR SOLVENT & UV INKS

Applications

Removes ink from the screen for quick color changes or clearing ink from stencil openings while on press.

Characteristics

- Recommended for use with solvent based and UV inks
- Flash point 43°C/109°F

Features/Benefits

- Versatile and with fast drying formula

Available formats: quart, gallon, 5 gallon, 55 gallon

DIRECTIONS FOR USE

Apply press wash directly to the screen with a low pressure sprayer, or a saturated wiping cloth. Wipe in a circular motion until ink has cleared. Allow to evaporate and continue printing.

ISC DEGREASERS

ISC BLOCKOUTS

ISC PRESS WASHES

ISC SCREEN WASHES

ISC STENCIL REMOVERS

ISC HAZE REMOVER



help@chromaline.com | www.chromaline.com

(800) 328-4261 | International: +1-218-628-2217

HEALTH & SAFETY: Before using, refer to the appropriate [Safety Data Sheets](#).

STORAGE: When sealed in the original container and stored in cool conditions, Chromaline's integrated Screen Chemistry will maintain their original properties for two years from the date of production.

Chroma/Screen Wash *ISC*

**UNIVERSAL INK REMOVER
WITH NO FOAM FOR AUTOMATIC CLEANING**

Applications

Removes plastisol, UV and water-based inks from the screen during the reclaiming process, either manually or in automatic systems.

Characteristics

- Flash point >200°F (93°C)
- No foam & low odor and can be used for manual or automatic cleaning

Features/Benefits

- Emulsifies for easy water rinsing and avoids formation of ghost images
- High efficiency formula reduces product consumption
- Universal performance reduces the need for multiple ink removers
- Can be re-applied after stencil removal to reduce ghost images

Available formats: quart, gallon, 5 gallon, 55 gallon

DIRECTIONS FOR USE

Use a spatula to scrape excess ink from screen. Apply the product to squeegee side of the screen. Use a nonabrasive brush to scrub both sides of the screen until the ink is liquefied. Starting from the bottom, rinse ink residue from the screen with water.

ISC DEGREASERS

ISC BLOCKOUTS

ISC PRESS WASHES

ISC SCREEN WASHES

ISC STENCIL REMOVERS

ISC HAZE REMOVER



help@chromaline.com | www.chromaline.com

(800) 328-4261 | International: +1-218-628-2217

HEALTH & SAFETY: Before using, refer to the appropriate [Safety Data Sheets](#).

STORAGE: When sealed in the original container and stored in cool conditions, Chromaline's integrated Screen Chemistry will maintain their original properties for two years from the date of production.

Chroma/Strip™ *ISC*

READY TO USE STENCIL REMOVER

- Fortified with surfactants for fast penetration
- Doesn't settle, no mixing required

Available formats: quart, gallon, 5 gallon, 50 gallon

DIRECTIONS FOR USE

Be sure all ink has been removed from the screen before reclaiming. Apply solution to both sides of the entire screen with a soft polyester scrub brush. Do not allow to dry on screen. Wait briefly, remove residue with high pressure water.

Chroma/Strip™ Plus *ISC*

STENCIL REMOVER CONCENTRATE

- Liquid concentrate that includes powerful built-in degreaser
- Dilute 35:1 by volume for manual spray application

Available formats: 5 oz, quart, 1.3 gallon

DIRECTIONS FOR USE

By volume, dilute 1 part of **Chroma/Strip™ Plus *ISC*** in 35 parts water for manual spray application.

Be sure all ink has been removed from the screen before reclaiming. Apply solution to both sides of the entire screen with a soft polyester scrub brush. Do not allow to dry on screen. Wait briefly, remove residue with high pressure water.

Auto Strip *ISC*

200:1 STENCIL REMOVER

- Super concentrated, low foaming formula
- Dilutes 40:1 by volume for manual spray application
- Dilutes up to 200:1 by volume for use in automated screen recycling systems
- Will not block spray nozzles

Available formats: gallon, 5 gallon

DIRECTIONS FOR USE

Auto Reclaim Systems

Dilute up to 1:200 parts water by volume for use in Automatic screen reclaiming machines, but optimal dilution ratio may vary based on equipment design and emulsion selection.

Manual Spray Application.

Dilute up to 1:40 parts water by volume. Be sure all ink has been removed from the screen before reclaiming. Apply solution to both sides of the entire screen with a soft polyester scrub brush. Do not allow to dry on screen. Wait briefly, remove residue with high pressure water.

Chroma/Dip *ISC*

DIP TANK RECLAIM SOLUTION

- Unlocks stencils and textile inks for easy one-step removal
- 10:1 Concentrate used for dip tank reclaiming of textile screens.
- Long lasting and economical

Available formats: gallon, 5 gallon

DIRECTIONS FOR USE

Dilute **Chroma/Dip *ISC*** up to 1:10 with water and fully immerse screens for 1 to 2 minutes. Remove screen and brush lightly to speed ink and stencil removal. Use pressure washer to remove all traces of ink and stencil. Do not allow solution to dry on the stencil.



help@chromaline.com | www.chromaline.com

(800) 328-4261 | International: +1-218-628-2217

ISC DEGREASERS

ISC BLOCKOUTS

ISC PRESS WASHES

ISC SCREEN WASHES

ISC STENCIL REMOVERS

ISC HAZE REMOVER

HEALTH & SAFETY: Before using, refer to the appropriate [Safety Data Sheets](#).

STORAGE: When sealed in the original container and stored in cool conditions, Chromaline's integrated Screen Chemistry will maintain their original properties for two years from the date of production.

Ghost/Buster *ISC*

HAZE REMOVER PASTE

Applications

Removes stains, haze, ghost images from mesh for screen recycling.

Characteristics

- Powerful fast acting gel works in minutes
- One part, ready to use formula removes the toughest stains
- Low odor during use with pressure washer

Features/Benefits

- Fast and easy application with stainless steel scoop coater
- Non-drip and works only where applied

Available formats: quart, gallon

DIRECTIONS FOR USE

After ink and stencil have been removed, dry the mesh, then spread gel on stained areas.

Apply by coating with stainless steel scoop coater, 2 coats on each side of screen, or spread gel on screen with brush or screen scrubber.

Wait and let **Ghost/Buster *ISC*** penetrate the stain for a period ranging from seven minutes to a maximum of ten minutes. Please note that exceeding ten minutes may begin to weaken the mesh.

Pressure rinse screen from bottom to top with a pressure washer keep nozzle close to screen. Flood rinse screen with a garden hose to remove any residue after the pressure rinse.

For very tough stains, dry screen before application.

***Caution: Irritant.** Avoid eye or skin contact, keep out of reach of children. Refer to container label or SDS for additional information



PRINT WITH CONFIDENCE



integrated Screen Chemistry

help@chromaline.com | www.chromaline.com

(800) 328-4261 | International: +1-218-628-2217

ISC DEGREASERS

ISC BLOCKOUTS

ISC PRESS WASHES

ISC SCREEN WASHES

ISC STENCIL REMOVERS

ISC HAZE REMOVER